



Spectrum^{XF}

The extra fast, built-to-last, performance-without-compromise scanner.

Extra Speed + New Camera + Onboard VRS = Performance without Compromise With scanning speeds up to 140 pages per minute, the new best-of-breed SharpShooter™ TriLinear CCD Camera, and Onboard VirtualReScan® (VRS) technology, Spectrum XF offers the best combination of features you'll find in a high-volume production scanner. Spectrum XF provides all of the extra benefits you want – extra throughput, extra efficiency, extra OCR, ICR and Barcode recognition – without the extra cost.

extra fast
10-30% faster
color, bitonal, grayscale
up to 140 ppm

built-to-last
exceptional durability
60,000 documents/day
600,000 scans/roller

peak-performance
best-of-breed camera
Onboard VRS
maximum OCR accuracy



**Ultrasonic Multifeed Detection & Ignore by Size:
Never Miss a Doublefeed**

Simply the best way to prevent multifeds and resolve them immediately should they occur. This innovation also allows documents with photographs, labels, taped receipts, and even envelopes, to be scanned automatically – without stopping, requiring user-intervention or having to manually turn sensors on and off.

**Prompt Resolution: Resolve Problems
without Rescanning or Restarting**

Prompt Resolution notifies the user of any jam, misfeed or paper handling issue, automatically deleting any bad images. Users then continue scanning where they left off – without having to rescan the entire batch.

Only Spectrum XF combines the benefits of color scanning with the efficiencies of bitonal scanning onboard the scanner so users can maximize speed, productivity, and image quality while minimizing file sizes, consumables and service costs. Like all Böwe Bell + Howell scanners, Spectrum XF offers users robust scanning capabilities while delivering huge savings in time, money and maintenance over the life of the scanner.

Spectrum XF and Böwe Bell + Howell. Always adding value.



Best-of-Breed CCD Camera Technology: Sharper Images at Top Speeds

Spectrum XF proves that going faster doesn't mean you have to sacrifice image quality. The state-of-the-art TriLinear camera design ensures images at a finer level of detail in bitonal and grayscale, and in more vivid color.

Unmatched power and speed:

- 600 dpi optical capture
- 40 megapixel-per-second throughput
- 22,500 total pixel capture
- 7,500 pixel capture per line

Better image quality also means higher accuracy for OCR, ICR and barcode recognition, a terrific advancement for forms processing applications.

Extra Advantages: Faster In Every Setting

Whatever your business or application, Spectrum XF will get you there... faster. With Spectrum XF, you can now take advantage of speeds up to 140 ppm (pages per minute). How much faster is this over previous models?

For capture users:

- 13-30% faster in color at 200 dpi
- 10-17% faster in bitonal at 200 dpi

For forms processing users:

- 12-15% faster in bitonal at 300 dpi

By any measure and at any setting, Spectrum XF is up to 20% faster than other scanners in its class.

Negative Inversion: Versatile Scanning

Spectrum XF allows users to convert black to white and vice versa when scanning images printed on paper that has a black or near-black background – a great feature for scanning micro-film printouts.



Onboard VirtualReScan: Maximize Efficiency without the Trade-Offs

Spectrum XF features Onboard VRS, which means that each model has a VRS board built-in. Simply put, an onboard implementation of VRS is the best way to take full advantage of all image enhancement and prompt resolution functionality that VRS has to offer – without sacrificing scanning speed. It's like having a PC inside your scanner, helping to drive performance and processing time with optimal speed and efficiency.

Scanners utilizing software-based VRS often have to sacrifice a measure of speed to accommodate image enhancement capabilities, such as cropping, deskew and brightness, particularly when scanning duplex, in color or both. In addition, scanners that were built without VRS in mind may not achieve desired performance levels because connectivity between the scanner and VRS has not been optimized. Because Böwe Bell + Howell was the first manufacturer to implement Onboard VRS as a standard feature over five years ago with the Copiscan 8000 Plus, no one has done it longer and no one does it better.

With Spectrum XF and Onboard VRS, you can have advanced speed and improved productivity at the same time, on one system – now that's performance without compromise.

Advanced Color Dropout: Exceptional Forms Processing

Spectrum XF allows users to dropout any color – not just to red, green, or blue – a great feature for users who want to drop out unnecessary color backgrounds altogether while capturing color information in the foreground.



Onboard Auto Color Detect: Color When You Want It, Bitonal When You Don't

Even if only a few of your documents need to be scanned in color, the advantages of onboard ACD are unmistakable.

By correctly identifying color and bitonal documents automatically, the time needed for scanning can be reduced by up to 60% over other methods. ACD eliminates the manual processing steps needed to capture color content on competitive scanning systems because the pre-sorting of color documents and inserting of separator sheets with patch codes is not necessary. And with ACD performed onboard in Spectrum XF, you won't have to sacrifice scanner speed to utilize it, which would negate the very productivity gains yielded by ACD.

Onboard Background Saturation and Dropout: Reduce File Size

Color Background Saturation and Dropout saves up to 40% in file space when scanning in color by allowing users to saturate or "smooth" document image backgrounds into one uniform color. This functionality not only makes images easier to read but also presents another way to stretch storage capacity, preserve only "mission critical" information and control storage costs.

Section 508 Compliance: Scan without Limits

Spectrum XF meets the standards of Section 508 of the Rehabilitation Act, with such features as Audible Tone Assistance and a Braille quick reference guide for the visually impaired, and a TTY technical support line for the audibly impaired at 847.423.3032.

Advanced Forms Processing: Maximize OCR, ICR and Barcode Recognition

Spectrum XF's accelerated scanning speeds – up to 95 ppm landscape and 78 ppm portrait in bitonal at 300 dpi combined with dramatic advances in image quality – deliver superior optical character recognition (OCR), intelligent character recognition (ICR) and barcode recognition rates.

Spectrum XF also allows users to dropout any color – not just red, green or blue. Organizations can now design forms using any color, preserve the information they need, and save file size.

HCFA Form
Scan forms with patch codes



Airbill
Capture handwriting and barcodes with greater accuracy



Invoice
Record financial documents quickly and easily





Spectrum^{XF}

Model		8140D		8120D		8090D	
Scanning Speed Letter Size Landscape / Portrait	Binary at 200 dpi	Simplex 140 / 115 ppm Duplex 280 / 230 ipm		Simplex 120 / 100 ppm Duplex 240 / 200 ipm		Simplex 90 / 75 ppm Duplex 180 / 150 ipm	
	Color at 150 dpi	Simplex 140 / 115 ppm Duplex 280 / 230 ipm		Simplex 120 / 100 ppm Duplex 240 / 200 ipm		Simplex 90 / 75 ppm Duplex 180 / 150 ipm	
Resolution		100-400 dpi Optical: 600 dpi					
Output Options		Bitonal, Grayscale (8 bit) and Color (24 bit)					
Image Enhancement and Advanced Color Functionality		 Cropping, Deskew, Brightness and Contrast Control				Auto Color Detect, Color Background Saturation and Dropout, Small Color Object Detection, Advanced Color Dropout	
Supported Drivers (Included)		ImageControls, ISIS, TWAIN					
Multifeed Detection		Ultrasonic Multifeed with Ignore by Size up to 10 in. (254 mm)					
Imprinting		Pre-Scan Standard		Pre-Scan Optional			
Document Size		2.6 x 2.6 in. (66 x 66 mm) to 11.7 x 40.0 in. (297 x 1,016 mm)					
Paper Thickness		0.0018 to 0.008 in. (0.046 to 0.20 mm)					
Paper Weight		9 to 110 lb bond					
Interface		68 pin SCSI III					
Feeder Capacity		500-Sheet Mode, 100-Sheet Mode, Manual Mode					
Scanner Size (HxWxD)		18 x 22.75 x 27.5 in. (45.72 x 57.79 x 69.85 cm)					
Scanner Weight		103 lbs (46.7 kg)					
Power Consumption	Voltage	120 V	240 V	120 V	240 V	120 V	240 V
	Maximum (Scanning)	220 W	224 W	220 W	224 W	210 W	214 W
	Minimum (Idle)	150 W	153 W	150 W	153 W	150 W	153 W
Environment	Temperature	60°F to 100°F (16°C to 37°C)					
	Relative Humidity	10% to 80% non-condensing					
Sound Output (SPL ref 20 µPa)	200 dpi	55.0 dBA					
	400 dpi	56.9 dBA					
Additional Features		User Replaceable Skimmer and Separator Rollers (last up to 600,000 scans of bond paper, 250,000 NCR paper) User Replaceable Lamps (last up to 5,000 hours)					
Additional Contents		Power Cord, Camera Calibration Kit, Operator Manual (in 7 languages), CD-ROM (Installation and Operation Manual, VRS, User Utility Software), Printed Documents (Manual, Quick Installation Guide and Warranty Card)					
Additional Options		Ultimate Scanning System 0103100 (WW), 0103101 (EU); Custom Table 0123070 (not available in Europe); All-In-One Consumables Kit S006600 (US), S006800 (WW); Extended Exit Tray 0123024; Continuous Feeder Tray 0123025; Dust Cover S005164					

© 2005 Bove Bell + Howell Scanners, L.L.C. All rights reserved. BÖWE BELL + HOWELL, SharpShooter, the B&H logo and the ACD magnifying glass logo are trademarks or registered trademarks of BBH, Inc. VirtualReScan and the VRS logo are registered trademarks of Kofax Imaging Products, Inc. All other trademarks and service marks are the property of their respective owners. Specifications are subject to change without notice.

Phone: 1.800.SCAN.494 or 1.847.423.3032 (TTY)
www.bbhscanners.com Form #SD-199-A/S006767



Böwe Bell+Howell Scanners. Always adding value.