fi-8170 Desktop Scanner

Professionals prefer the fi-8170.

Get your work done right the first time, faster, with less processing pain.



Key Features

- Compatible with the PaperStream Software Suite and supported integrations
- Clear Image Capture (CIC) + PaperStream IP = unmatched image performance
- Automatic Deskew and Overscan Control keep documents and data aligned for complete capture without rescans
- Scan IDs, passports, and pamphlets without skipping a beat, thanks to Manual Feed Mode
- Protect paper and data with Automatic Separation Control, Intelligent Multi-Feed Detection, and Intelligent Sonic Paper Protection (ISOP)

Better Together

Maximize scanner performance and ROI. Bundle scanner, service, and a powerful PaperStream software solution. Learn more at sales@pfu-us.ricoh.com





Superior tech can improve AI outcomes







Load Documents

Speed and accuracy win in workflows. Get the paper protection and versatility needed to ensure you get actionable data.

Scan with Intelligence

Maximize mined data with pristine image quality. You can't use data your scanner doesn't capture.

Export or Distribute

Success is structured. Find dollars in the details with data that is where you need it when you need it.





RICOH fi-8170 desktop scanner

Technical Information



Image Sensor Type	CIS x 2 (front x 1, back x 1)	Image Processing Functions	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis, Dropout color (None/Red/Green/Blue/White/Saturation/Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge filler, Vertical streaks reduction, Background pattern removal, Cropping, Static threshold
Light Source	RGB LED x 2 (front x 1, back x 1)		
Document Size	Maximum: 215.9 x 355.6 mm (8.5 x 14 in.) Minimum: 48 x 50 mm (1.9 x 2 in.) Long Page Scanning: Up to 6,096 mm (240 in.)		
Paper Weight (Thickness)	Plastic Card: 1.4 mm or less Paper: 20 to 465 g/m² (5.3 to 124 lb) Booklet: Less than 7 mm thick	Included Software / Drivers	PaperStream IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver, Image Scanner Driver for macOS (ICA), Image Scanner Driver for Linux (SANE), PaperStream Capture, PaperStream ClickScan, Software Operation Panel, Error Recovery Guide, ABBYY FineReader for ScanSnap™, PaperStream Central Admin
Scanning Speed (A4 Portrait, Color/Grayscale/ Monochrome)	Simplex: 70 ppm (200/300 dpi) Duplex: 140 ipm (200/300 dpi)		
ADF Capacity	100 sheets (A4 80 g/m ² or Letter 20 lb		Windows® 11, 10, 8.1, 7
Background Colors	White / Black (selectable)	Supported Operating Systems	Windows Server® 2025, 2022, 2019, 2016,
Optical Resolution	600 dpi	Systems	2012 R2, 2012, macOS, Linux (Ubuntu)
	50 to 600 dpi (adjustable by 1 dpi increments), 1200 dpi (driver)	Included Items Options	ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM
Output Format	Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit	Post Imprinter	FI-819PRB
Interface	USB 3.2 Gen1x1 / USB 2.0 / USB 1.1 Ethernet: 10BASE-T, 100BASE-TX, 1000BASE-T (auto-negotiation)	PaperStream Capture Pro	PSC-PRO-1Y, PSC-PRO-3Y, PSC-PRO-5Y
		PaperStream Capture Pro Premium	PSC-PREM-1Y, PSC-PREM-3Y, PSC-PREM-5Y
Power Requirements	AC 100V - 240V 50/60 Hz	Deluxe Bundle	CG01000-310299, with 2 Years
Power Consumption	Operating: 28 W or less / Eco mode: 17 W Sleep Mode: 2.0 W or less (LAN) / 1.4 W or less (USB) Auto Standby: 0.2 W or less	Consumables	PaperStream Capture Pro
		Pick Roller	PA03670-0002: Every 200,000 sheets or 1 year
		Brake Roller	PA03810-0001: Every 200,000 sheets or 1 year
Operating Environment	Temperature: 5 to 35 °C (41 to 95 °F) Relative Humidity: 15 to 80%	Print Cartridge	CA00050-0262: 4,000,000 characters or 6 months
	(non-condensing)	Booklet Carrier Sheet	PA03810-0020: Pack of 1
Dimensions (W x D x H)	300 x 170 x 163 mm (11.8 x 6.7 x 6.4 in.)	Photo Carrier Sheets	PA03770-0015: Pack of 3
Weight	4 kg (8.8 lb)	Carrier Sheets	PA03360-0013: Pack of 5
Environmental Compliance	ENERGY STAR®, ROHS	Services	CO170 AFDVANIDD 1 CO170 AFVANADD 2
Multifeed Detection	Ultrasonic sensor	Advance Exchange	S8170-AEPWNBD-1, S8170-AEMYNBD-3, S8170-AEMYNBD-5
	(Overlap), Length detection	Depot Mail-in Repair	S8170-DEPW5DY-3
Paper Protection	Image monitoring, Sound detection (iSOP)	Standard Warranty	3 Year Advance Unit Replacement

Trademarks ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. macOS is a trademark of Apple Inc., registered in the U.S. and other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.











^{*} Please find Safety Precautions, ENERGY STAR, and EPEAT Information at https://pages.pfuricoh.com/safety-precautions-energy-star-and-epeat-information